Style Name	PROFUSION 20	
Style Number	54933	
Product Type	Broadloom	
Construction	Level Loop	
Fiber	100% Pivotal™	
Dye Method	Solution Dyed	
Primary Backing	Synthetic	
Secondary Backing	Classicbac	
Traffic Rating	Moderate	
	U.S.	Metric
Product Size	12 ft	3.66 m
Gauge	1/10 in	39.37 per 10 cm
Stitches	10 per in	41 per 10 cm
Finished Pile Thickness	0.141 in	3.58 mm
Average Density	5106 oz/yd³	
Total Thickness	0.284 in	7.21 mm
Tufted Weight	20 oz/yd²	678.1 g/m²



Recommended Installation Methods

Direct Glue

Performance Testing

Pill Test	Pass
Radiant Panel	Class I
NBS Smoke	Less than 450
Electrostatic Propensity	Less than 3.5 kv
CRI Greenlabel Plus	GLP9970
ADA Compliance	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

Broadloom 10 year Commercial Limited Warranty with Stain and Color

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.